



FLEX-IQ[®] Technology

SMART SOLUTIONS READY FOR TOMORROW



Time saving solutions combined with very high quality, flexibility, reliability and durability for all sealant jobs.

Benefits: Friendlier to use, for human and nature. Easier and quicker to apply, time saving. Perfect finish and appearance, high end. High movement capability, extreme flexible. Extreme great performance. Durable and sustainable, long lasting. CE marked.



	SEAL'N'FLEX ONE PLUS P590	SEAL'N'FLEX PREMIUM P795	SEAL'N'FLEX FACADE H725	SEAL'N'FLEX PRO SEAL H760	SEAL'N'FLEX WEATHER SHIELD H985
CE classification	EN 15651-1: F-EXT INT CC 25LM EN 15651-4: PW-EXT INT CC 25LM	EN 15651-1: F-EXT INT CC 25HM EN 15651-4: PW-EXT INT CC 25HM	EN 15651-1: F-EXT INT CC 25LM EN 15651-4: PW-EXT INT CC 25LM	EN 15651-1: F-EXT INT CC 25HM EN 15651-4: PW-EXT INT CC 25HM	EN 15651-1: F-EXT INT CC 25LM EN 15651-4: PW-EXT INT CC 25LM
Certifications	French A+	Emicode EC2 French A+	Emicode EC1 Plus French A+	Emicode EC1 Plus French A+	Emicode EC1 Plus M1 French A+
ASTM C920	Class 50	Class 50	Class 50	-	-
Label free Technology	yes	yes	yes	yes	yes
Elongation @ Break	New Gen PU > 1000%	New Gen PU > 500%	Hybrid > 600%	Hybrid > 450%	Hybrid > 850%
Tensile Strength	1,2 N/mm ²	0,72 N/mm ²	1,3 N/mm ²	1,2 N/mm ²	1,4 N/mm ²

For more product information, application videos, certifications, please visit our global website

www.bostik.com